

# **MATERIAL SAFETY DATA SHEET (MSDS) FOR PORTLAND CEMENT**

(Complies with OSHA and MSHA Hazard Communication Standards,  
29 CFR 1910.1200 and 30 CFR Part 47)



**CEMEX, INC.  
ODESSA CEMENT PLANT  
P.O. BOX 1547  
ODESSA, TEXAS 79760**

---

## Section 1 - IDENTIFICATION

### Supplier/Manufacturer

CEMEX, Inc.  
Odessa Cement Plant  
P.O. Box 1547  
Odessa, Texas 79760

### Emergency Contact Information

(915) 385-2800  
(800) 927-4838 (24-hour number)

### Chemical name and synonyms

Portland Cement (CAS #65997-15-1)

### Product name

"CEMEX Type I"  
"CEMEX Type I/II"  
"CEMEX Type III"  
"CEMEX Type V"  
"CEMEX Class C" (Oil Well Cement)  
"CEMEX Class H" (Oil Well Cement)  
"CEMEX Class A" (Oil Well Cement)

### Chemical family

Calcium salts.

### Formula

3CaO.SiO <sub>2</sub>	(CAS #12168-85-3)
2CaO.SiO <sub>2</sub>	(CAS #10034-77-2)
3CaO.Al <sub>2</sub> O <sub>2</sub>	(CAS #12042-78-3)
4CaO..Al <sub>2</sub> O <sub>3</sub> Fe <sub>2</sub> O <sub>3</sub>	(CAS #12068-35-8)
CaSO <sub>2</sub> .2H <sub>2</sub> O	(CAS #13397-24-5)

Other salts:

Small amounts of MgO, and trace amounts of K<sub>2</sub>SO<sub>4</sub> and Na<sub>2</sub>SO<sub>4</sub> may also be present.

---

## Section 2 - COMPONENTS

### Hazardous Ingredients

Portland cement clinker (CAS# 65997-15- 1) - approximately 93.5-96.0 % by weight

ACGIH TLV-TWA (2000) = 10 mg total dust/m<sup>3</sup>  
OSHA PEL (8-hour TWA) = 50 million particles/ft<sup>3</sup>

Gypsum/Calcium Sulfate Dihydrate (CAS# 7778-18-9) - approximately - 4.0-6.5 % by weight

ACGIH TLV-TWA (2000) = 10 mg total dust/m<sup>3</sup>  
OSHA PEL (8-hour TWA) = 15 mg total dust/m<sup>3</sup>  
OSHA PEL (8-hour TWA) = 5 mg respirable dust/m<sup>3</sup>

Respirable quartz (CAS# 14808-60-7) - approximately - 0.02-0.04 % by weight

ACGIH TLV-TWA (2006) = 0.025 mg respirable quartz dust/m<sup>3</sup>  
OSHA PEL (8-hour TWA) = (10 mg respirable dust/m<sup>3</sup>)/(percent silica + 2)

### Trace Ingredients

Trace amounts of naturally occurring chemicals might be detected during chemical analysis. Trace constituents may include up to 0.75% insoluble residue, some of which may be free crystalline silica, calcium oxide (Also known as lime or quick lime), magnesium oxide, potassium sulfate, sodium sulfate, chromium compounds, and nickel compounds.

---

## Section 3 - HAZARD IDENTIFICATION

### Emergency Overview

Portland cement is a light gray powder that poses little immediate hazard. A single short-term exposure to the dry powder is not likely to cause serious harm. However, exposure of sufficient duration to wet portland cement can cause serious, potentially irreversible tissue (skin or eye) destruction in the form of chemical (caustic) burns. The same type of tissue destruction can occur if wet or moist areas of the body are exposed for sufficient duration to dry portland cement.

### Potential Health Effects

#### **Relevant Routes of Exposure:**

Eye contact, skin contact, inhalation, and ingestion.

#### **Effects Resulting from Eye Contact:**

Exposure to airborne dust may cause immediate or delayed irritation or inflammation. Eye contact by large amounts of dry powder or splashes of wet portland cement may cause effects ranging from moderate eye irritation to chemical burns or blindness. Such exposures require immediate first aid (see Section 4) and medical attention to prevent significant damage to the eye.

#### **Effects Resulting from Skin Contact:**

Discomfort or pain cannot be relied upon to alert a person to hazardous skin exposure. Consequently, the only effective means of avoiding skin injury or illness involves minimizing skin contact, particularly with wet cement. Exposed persons may not feel discomfort until hours after the exposure has ended and significant injury has occurred.

Dry portland cement contacting wet skin or exposure to moist or wet portland cement may cause more severe skin effects including thickening, cracking or fissuring of the skin. Prolonged exposure can cause severe skin damage in the form of (alkali) chemical burns.

Some individuals may exhibit an allergic response upon exposure to portland cement, possibly due to trace elements of chromium. The response may appear in a variety of forms ranging from a mild rash to severe skin ulcers. Persons already sensitized may react to their first contact with the product. Other persons may first experience this effect after years of contact with portland cement products.

#### **Effects Resulting from Inhalation:**

Portland cement may contain trace amounts of free crystalline silica. Prolonged exposure to respirable free silica can aggravate other lung conditions and cause silicosis, a disabling and potentially fatal lung disease.

Exposure to portland cement may cause irritation to the moist mucous membranes of the nose, throat, and upper respiratory system. It may also leave unpleasant deposits in the nose.

#### **Effects Resulting from Ingestion:**

Although small quantities of dust are not known to be harmful, ill effects are possible if larger quantities are consumed. Portland cement should not be eaten.

#### **Carcinogenic potential:**

Portland cement is **not** listed as a carcinogen by NTP, OSHA, or IARC. It may however, contain trace amounts of substances listed as carcinogens by these organizations.

Crystalline silica, a potential trace level contaminant in Portland cement, is now classified by IARC as known human carcinogen (Group I). NTP has characterized respirable silica as "reasonably anticipated to be [a] carcinogen".

#### **Medical conditions which may be aggravated by, inhalation or dermal exposure:**

Pre-existing upper respiratory and lung diseases.

Unusual (hyper) sensitivity to hexavalent chromium (chromium<sup>+6</sup>) salts.

---

## Section 4 - FIRST AID

### Eyes

Immediately flush eyes thoroughly with water. Continue flushing eye for at least 15 minutes, including under lids, to remove all particles. Call physician immediately.

### Skin

Wash skin with cool water and pH-neutral soap or a mild detergent. Seek medical treatment in all cases of prolonged exposure to wet cement, cement mixtures, liquids from fresh cement products, or prolonged wet skin exposure to dry cement.

### Inhalation of Airborne Dust

Remove to fresh air. Seek medical help if coughing and other symptoms do not subside.

### Ingestion

Do not induce vomiting. If conscious, have the victim drink plenty of water and call a physician immediately.

---

## Section 5 - FIRE AND EXPLOSION DATA

Flash point .....	None	Lower Explosive Limit.....	None
Upper Explosive Limit.....	None	Auto ignition temperature.....	Not Combustible
Extinguishing media.....	Not Combustible	Special fire fighting Procedures.....	None
Hazardous combustion products..	None	Unusual fire and explosion hazards...	None

---

## Section 6 - ACCIDENTAL RELEASE MEASURES

Collect dry material using a scoop. Avoid actions that cause dust to become airborne. Avoid inhalation of dust and contact with skin. Wear appropriate personal protective equipment as described in Section 8.

Scrape up wet material and place in an appropriate container. Allow the material to "dry" before disposal. Do not attempt to wash portland cement down drains.

Dispose of waste material according to local, state and federal regulations.

---

## Section 7 - HANDLING AND STORAGE

Keep portland cement dry until used. Normal temperatures and pressures do not affect the material.

Promptly remove dusty clothing or clothing which is wet with cement fluids and launder before reuse. Wash thoroughly after exposure to dust or wet cement mixtures or fluids.

---

## Section 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

### Skin Protection

Prevention is essential to avoiding potentially severe skin injury. Avoid contact with unhardened portland cement. If contact occurs, promptly wash affected area with soap and water. Where prolonged exposure to unhardened portland cement products might occur, wear impervious clothing and gloves to eliminate skin contact. Wear sturdy boots that are impervious to water to eliminate foot and ankle exposure.

Do not rely on barrier creams: barrier creams should not be used in place of gloves.

Periodically wash areas contacted by dry portland cement or by wet cement or concrete fluids with a pH neutral soap. Wash again at the end of work. If irritation occurs, immediately wash the affected area and seek treatment. If clothing becomes saturated with wet concrete, it should be removed and replaced with clean dry clothing.

### Respiratory Protection

Avoid actions that cause dust to become airborne. Use local or general exhaust ventilation to control exposures below applicable exposure limits.

Use NIOSH/MSHA approved (under 30 CFR 11) or NIOSH approved (under 42 CFR 84) respirators in poorly ventilated areas, if

an applicable exposure limit is exceeded, or when dust causes discomfort or irritation. (Advisory: Respirators and filters purchased after June 10, 1998 must be certified under 42 CFR 84.)

#### Ventilation

Use local exhaust or general dilution ventilation to control exposure within applicable limits.

#### Eye Protection

Where potentially subject to splashes or puffs of cement, wear safety glasses with side shields or goggles. In extremely dusty environments and unpredictable environments wear unvented or indirectly vented goggles to avoid eye irritation or injury. Contact lenses should not be worn when working with portland cement or fresh cement products.

---

### **Section 9 - PHYSICAL AND CHEMICAL, PROPERTIES**

Appearance.....	Gray Powder	Odor.....	No distinct odor
Physical state.....	Solid (powder)	pH (in water).....	12 to 13
Solubility in water...	Slightly soluble (0.1 to 1.0%)	Vapor pressure.....	Not applicable
Vapor density.....	Not applicable	Boiling point.....	Not applicable (i.e., > 1000 C)
Melting point.....	Not applicable	Specific gravity (H2O = 1.0).....	3.15
Evaporation rate.....	Not applicable		

---

### **Section 10 - STABILITY AND REACTIVITY**

#### Stability

Stable.

#### Conditions to avoid

Unintentional contact with water.

#### Incompatibility

Wet Portland cement is alkaline. As such it is incompatible with acids, ammonium salts and phosphorous.

#### Hazardous decomposition

Will not spontaneously occur. Adding water produces (caustic) calcium hydroxide

#### Hazardous Polymerization

Will not occur.

---

### **Section 11 - TOXICOLOGICAL INFORMATION**

For a description of available, more detailed toxicological information contact the supplier or manufacturer.

---

### **Section 12 - ECOLOGICAL INFORMATION**

#### Ecotoxicity

No recognized unusual toxicity to plants or animals

#### Relevant physical and chemical properties

(See Sections 9 and 10.)

---

### **Section 13 - DISPOSAL**

Dispose of waste material according to local, state and federal regulations. (Since portland cement is stable, uncontaminated material may be saved for future use.

Dispose of bags in an approved landfill or incinerator.

---

### **Section 14 - TRANSPORTATION DATA**

#### Hazardous materials description/proper shipping name

Portland cement is not hazardous under U.S. Department of Transportation (DOT) regulations.

Hazard class

Not applicable

Identification number

Not applicable.

Required label text

Not applicable.

Hazardous substances/reportable quantities (RQ)

Not applicable.

---

**Section 15 - OTHER REGULATORY INFORMATION**

Status under USDOL-OSHA Hazard Communication Rule, 29 CFR 1910.1200

Portland cement is considered a "hazardous chemical" under this regulation, and should be part of any hazard communication program.

Status under CERCLA/SUPERFUND 40 CFR 117 and 302

Not listed.

Hazard Category under SARA(Title III), Sections 311 and 312

Portland cement qualifies as a "hazardous substance" with delayed health effects.

Status under SARA (Title III), Section 313

Not subject to reporting requirements under Section 313.

Status under TSCA (as of May 1997)

Some substances in portland cement are on the TSCA inventory list.

Status under the Federal Hazardous Substances Act

Portland cement is a "hazardous substance" subject to statutes promulgated under the subject act.

Status under California Proposition 65

This product contains up to 0.05 percent of chemicals (trace elements) known to the State of California to cause cancer, birth defects or other reproductive harm. California law requires the manufacturer to give the above warning in the absence of definitive testing to prove that the defined risks do not exist.

---

**Section 16 - OTHER INFORMATION**

Prepared by

Kevin Keegan  
Director - Health and Safety  
CEMEX, Inc.  
Houston, Texas

Approval date or Revision date

August, 1997

Date of previous MSDS

Approved: March 1991  
Revised: January 2008

Other important information

Portland cement should only be used by knowledgeable persons. A key to using the product safely requires the user to recognize that portland cement chemically reacts with water, and that some of the intermediate products of this reaction (that is those present while a portland cement product is "setting") pose a more severe hazard than does dry portland cement itself.

While the information provided in this material safety data sheet is believed to provide a useful summary of the hazards of portland cement as it is commonly used, the sheet cannot anticipate and provide the all of the information that might be needed in every situation. Inexperienced product users should obtain proper training before using this product.

SELLER MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY CEMEX, Inc. except that the product shall conform to contracted specifications. The information provided herein was believed by CEMEX, Inc. to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information to comply with all laws and procedures applicable to the safe handling and use of product and to determine the suitability of the product for its intended use. Buyer's exclusive remedy shall be for damages and no claim of any kind, whether as to product delivered or for non-delivery of product, and whether based on contract, breach of warranty, negligence, or otherwise shall be greater in amount than the purchase price of the quantity of product in respect of which damages are claimed. In no event shall Seller be liable for incidental or consequential damages, whether Buyer's claim is based on contract, breach of warranty, negligence or otherwise.

In particular, the data furnished in this sheet do not address hazards that may be posed by other materials mixed with portland cement to produce portland cement products. Users should review other relevant material safety data sheets before working with this portland cement or working on portland cement products, for example, portland cement concrete.